



# Safety Data Sheet

## KEX Tire Repair Materials

Product #: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 5

Rev. Date: 1/13/2017

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** KEX Leak Detector

**Chemical Family:** Aqueous glycol & Aromatic compounds solution

**Product Use:** Tire Leak Detection

**Restrictions on Use:** Use as directed by manufacturer

**Manufacturer:** KEX Tire Repair  
119 Rockland Ave.  
Northvale, NJ 07647  
Phone: 201 256-8200

**24-Hour Emergency Phone Number:** North America: 800-424-9300 (CHEMTREC)  
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

### 2. HAZARD IDENTIFICATION

#### GHS Classification

#### Health Hazards

Eye Irritation, Category 2B

#### GHS Labeling

#### Pictograms:



**Signal Word:** Warning!

#### Hazard Statements

H320: Causes eye irritation



# Safety Data Sheet

## KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 5

Rev. Date: 1/13/2017

### Precautionary Statements

#### Prevention:

P233: Keep container tightly closed.

P264: Wash hands and exposed skin thoroughly after handling.

P280: Wear protective gloves and eye protection

#### Response:

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313: If eye irritation persists: Get medical advice/attention.

#### Storage:

P403 + P233: Store in a well-ventilated place. Keep container tightly closed.

#### Disposal:

P501: Dispose of contents/container in accordance with local/regional/national regulations.

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### Chemical characterization

Glycol & Aromatic compounds solution

Component*	CAS #	Weight %
Propylene Glycol	57-55-6	1 - 5
Sodium Dodecylbenzenesulfonate	68081-81-2	1 - 5

\*The above listed components are OSHA hazardous materials which contribute to this products' GHS Hazard Categorization as prescribed in OSHA's Hazard Communication 29 CFR 1910.1200.

### 4. FIRST AID MEASURES

#### Inhalation

**Symptoms & Effects:** May cause irritation of the nose and airways, headache, coughing

**Measures:** Move outdoors or to fresh air. If not breathing or if breathing is difficult, provide artificial respiration or oxygen. If irritation occurs, seek medical attention.

#### Skin Contact

**Symptoms & Effects:** Slight skin irritation or burning sensation, redness.

**Measures:** Wash contaminated areas with mild soap and water after use. Wash contaminated clothing before reuse. If skin irritation occurs, seek medical attention.

#### Eye Contact

**Symptoms & Effects:** Eye irritation, stinging sensation, tearing, and redness, and swelling of the eyes.



# Safety Data Sheet

## KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 5

Rev. Date: 1/13/2017

**Measures:** Immediately flush eyes gently with plenty of water for at least 15 minutes. While washing, remove contact lenses if present and easy to do so and continue rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while washing. Seek medical attention.

### **Ingestion**

**Symptoms & Effects:** Stomach or intestinal irritation, nausea, vomiting, abdominal cramps, diarrhea, lumbar pain, dizziness, drowsiness

**Measures:** Seek immediate medical attention. Do NOT induce vomiting. If awake and alert, rinse mouth and drink 1 glass of water to help dilute the material. Do not give liquids to a drowsy or unconscious person. If vomiting occurs, keep heads below hips to prevent aspiration.

## **5. FIRE FIGHTING MEASURES**

**Suitable Extinguishing Media:** Alcohol-resistant foam, Water spray, Fog, Carbon dioxide, Dry chemical

**Unsuitable Extinguishing Media:** None identified

**Hazardous Combustion Products:** Hydrocarbons, Carbon monoxide, Carbon dioxide

**Protective Equipment for Fire-Fighters:** Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

**Precautions for Fire-Fighters:** This product does not burn, however heating may release vapors which can be ignited.

## **6. ACCIDENTAL RELEASE MEASURES**

**Protective Equipment:** Recommended to wear chemical splash goggles & gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to reduce skin exposure, such as long-sleeves and pants.

**Personal Precautions:** Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation.

**Environmental Precautions:** Do not allow discharge into drains, surface waters, or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

**Methods & Materials for Clean-Up:** Absorb material with inert materials. Shovel or gather material and place in appropriate container for disposal. Wash spill area thoroughly.



# Safety Data Sheet

## KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 5

Rev. Date: 1/13/2017

### 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes, skin and clothing. Wear proper personal protective equipment when handling this product. Do not eat, drink or smoke when using this product. Wash hands and face after handling this product and before eating, drinking, and smoking.

**Storage:** Keep container tightly closed away from direct sunlight. Keep away from food, drink, and animal foodstuffs.

**Incompatible Materials:** Strong oxidizing agents, Strong acids

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Exposure Limits :**

Exposure Limits have not been established for this product or any of its components.

**Engineering Controls:** Use product in a well-ventilated area.

**Occupational Exposure Controls:** Consider all potential hazards of this material, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Protective and Hygiene Measures:** Wash hands before breaks and after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

**Eye Protection:** Recommended to wear chemical splash goggles when there is potential for the exposure of the eyes to the product. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

**Hand Protection:** Recommended to wear gloves when using this product, and to discard of gloves that show tears, pinholes, or signs of wear.

**Skin Protection:** Recommended to wear long-sleeved clothing, pants and proper foot covering in order to minimize direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

**Respiratory Protection:** Not required.



# Safety Data Sheet

## KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 5

Rev. Date: 1/13/2017

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Pale liquid

**Odor:** Mild

**Odor Threshold:** No data available

**pH:** 7 - 8 (Calculated)

**Melting Point:** No data available

**Freezing point:** No data available

**Initial boiling point:** No data available

**Boiling range:** 212°F (100°C)

**Flash point (Tag closed cup):** Not applicable

**Evaporation rate:** No data available

**Flammability: Lower Limit:** Not applicable **Upper Limit:** Not applicable

**Vapor pressure:** < 0.1 psi

**Vapor density:** No data available

**Relative density:** 1.0 g/cm<sup>3</sup> (8.3 lb/gal)

**Solubility in water:** Completely Soluble

**Partition coefficient (n-octanol/water):** No data available

**Auto-ignition temperature:** No data available

**Decomposition temperature:** No data available

**Viscosity (dynamic):** No data available

### 10. STABILITY AND REACTIVITY

**Reactivity:** No decomposition if stored and applied as directed.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Will not react under normal conditions.

**Conditions to Avoid:** Excessive heat

**Incompatible Materials:** Strong oxidizing agents, Strong acids

**Hazardous decomposition products:** Hydrocarbons, Carbon monoxide, Carbon dioxide

### 11. TOXICOLOGICAL INFORMATION

**Primary Routes of Exposure:** Skin contact, Eye contact, Ingestion, Inhalation

**Symptoms Related to Physical, Chemical and Toxicological Characteristics:** Nausea, irritation of the nose, throat and airways, dizziness, drowsiness, headache, defatting of the skin, irritation to the digestive tract



# Safety Data Sheet

## KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 5

Rev. Date: 1/13/2017

### Measures of Toxicity:

Acute toxicities are calculated based on component toxicities

Mixture: Acute Oral Toxicity: No data available

Acute Dermal Toxicity: No data available

Acute Inhalation Toxicity: No data available

### Propylene Glycol

CAS # 57-55-6

Acute Oral Toxicity

LD<sub>50</sub> Rat: 20,000 mg/kg

Acute Dermal Toxicity

LD<sub>50</sub> Rat: 20,800 mg/kg

Acute Inhalation Toxicity

No Data Available

### Carcinogen Claims:

OSHA: No

International Agency for Research on Cancer (IARC): No; 4 [Probably Not Carcinogenic]

ACGIH: No; A5 [Not Suspected]

National Toxicology Program (NTP) Report on Carcinogens: No

## 12. ECOLOGICAL INFORMATION

**Eco-toxicity:** This substance may be harmful to aquatic organisms. It is strongly advised that this substance does not enter the environment.

### Propylene Glycol

CAS # 57-55-6

Toxicity to Fish

LC<sub>50</sub> – 52,930 mg/l (Fathead Minnow; 96 h)

Toxicity to Daphnia

EC<sub>50</sub> – > 10,000 mg/l (Daphnia; 48 h)

**Persistence & Degradability:** No data available

**Bio-accumulative Potential:** No data available

**Mobility in Soil:** No data available

**Other Adverse Effects:** No data available

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.

Contaminated packaging should be emptied as far as possible before disposal.



# Safety Data Sheet

## KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 5

Rev. Date: 1/13/2017

---

### 14. TRANSPORT INFORMATION

#### **DOT SHIPPING CLASSIFICATION:**

This product is not regulated as a hazardous material for transport.

#### **IMDG (Marine) SHIPPING CLASSIFICATION:**

This product is not regulated as a dangerous good for transport.

#### **IATA (Air) SHIPPING CLASSIFICATION:**

This product is not regulated as a dangerous good for transport.

### 15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

#### **SARA Title III**

##### **Section 302 – Extremely Hazardous Chemicals**

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

*None Listed*

##### **Section 313 – Toxic Chemicals**

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

*None Listed*

#### **OTHER FEDERAL REGULATIONS**

Components of this product are subject to RCRA Hazardous Waste requirements. Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

#### **CANADIAN REGULATIONS**

WHMIS Classification: Same as OSHA GHS classification

#### **STATE REGULATIONS**

##### California Proposition 65

This product does not contain materials known to the state of California to cause cancer, birth defects, and other reproductive harm.



# Safety Data Sheet

## KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 5

Rev. Date: 1/13/2017

The components of this product may be included on the various state hazardous materials lists noted below.  
New Jersey RTK Hazardous Substances List  
Pennsylvania Hazardous Substances List  
Vermont Hazardous Air Contaminants  
Washington Toxic Air Pollutants

**Note:** Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.

### **16. OTHER INFORMATION**

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

**MEDICAL EMERGENCIES:**

Call CHEMTREC 24 hours a  
Day for emergency information  
800-424-9300

**FOR ANY OTHER INFORMATION:**

**KEX TIRE REPAIR**  
119 Rockland Ave.  
NORTHVALE, NJ 07647  
201-256-8200

**NOTICE:** KEX TIRE REPAIR believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

**NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.**